



# HOT WELL DROP-INS

## Electric Sealed Well Hot Food Drop-In Units

- 304 Stainless Steel Top
- Fiberglass Insulation Between Compartments
- 12" X 20" Die Stamped Pan Openings
- 6" Deep Units

- 1" I.p.s. Drain
- Remote Control Panel
- Infinite Control Knobs
- Indicator Lights



Individual Sealed Well  
Compartments



DISW-3-120 Shown

### STANDARD DROP-IN UNITS

Model #	Price	Length	Width	# of Wells	Cut-Out Size W x L	Volts	Amps	Watts	Approx. Wt.	Cu. Ft.
DISW-1-120	\$2101	15-1/2"	24-1/2"	1	23-1/2" x 15-5/8"	120	9.17	1100	73 lbs.	6
DISW-2-120	3039	30-1/2"	24-1/2"	2	23-1/2" x 29-5/8"	120	12.34	2200	110 lbs.	6
DISW-3-120	3689	44-1/2"	24-1/2"	3	23-1/2" x 43-5/8"	120	27.51	3300	135 lbs.	6
DISW-1-240	2101	15-1/2"	24-1/2"	1	23-1/2" x 15-5/8"	208/240	3.97/4.58	825/1100	73 lbs.	6
DISW-2-240	3039	30-1/2"	24-1/2"	2	23-1/2" x 29-5/8"	208/240	7.94/9.16	1650/2200	110 lbs.	6
DISW-3-240	3689	44-1/2"	24-1/2"	3	23-1/2" x 43-5/8"	208/240	11.91/13.74	2475/3300	135 lbs.	18
DISW-4-240	4382	58-1/2"	24-1/2"	4	23-1/2" x 57-5/8"	208/240	15.88/18.32	3300/4400	180 lbs.	23
DISW-5-240	5706	72-1/2"	24-1/2"	5	23-1/2" x 71-5/8"	208/240	19.85/22.90	4125/5500	208 lbs.	35
DISW-6-240*	6729	86-1/2"	24-1/2"	6	23-1/2" x 85-5/8"	208/240	23.82/27.48	4950/6600	275 lbs.	35

\*6-well unit include two sets of control panels

**NOTE: Units are not designed to cook or heat frozen or refrigerated foods. Food placed in tables should already be hot, and the table will maintain the proper temperatures**



DISLSW-2-120 Shown

### SLIMLINE DROP-IN UNITS

Model #	Price	Length	Width	# of Wells	Cut-Out Size W x L	Volts	Amps	Watts	Approx. Wt.	Cu. Ft.
DISLSW-2-120	\$3361	46-1/2"	16-1/2"	2	15-1/4" x 45-1/4"	120	18.34	2200	95 lbs.	11
DISLSW-3-120	4033	68-1/2"	16-1/2"	3	15-1/4" x 67-1/4"	120	27.51	3300	125 lbs.	11
DISLSW-2-240	3361	46-1/2"	16-1/2"	2	15-1/4" x 45-1/4"	208/240	3.94/9.16	1600/2200	95 lbs.	18
DISLSW-3-240	4033	68-1/2"	16-1/2"	3	15-1/4" x 67-1/4"	208/240	11.90/13.34	2475/3300	150 lbs.	18
DISLSW-4-240	5663	90-1/2"	16-1/2"	4	15-1/4" x 89-1/4"	208/240	15.88/18.32	3300/4400	155 lbs.	23

### Drop-In Unit Options & Accessories

**Drop-In Units to be hard wired in the field. Please consult the factory for more information.**



**NEMA 5-15P**  
**SU-P-234**

1 well, 120v Units



**NEMA L5-30P**  
**SU-P-232**

1, 2, 3 or 6 well, 240v Units  
(6 well unit requires 2 Cords)



**NEMA 6-20P**  
**SU-P-231**

2 or 3 well, 120v Units



**NEMA L6-30P**  
**SU-P-233**

4 or 5 well, 240v Units

#### Autofill Upgrade

Automatically fills & maintains water level. For DISW, DISLSW, SW & HDSW Series. Requires added cost Manifold Drain Assembly (Except HDSW series). See below.

**SU-90 \$1980** Autofill Only



#### Manifold Drain Assembly

Add The Suffix **-M** To The Model Number And Add Additional Pricing Below.

**\$242** Per Well

#### Filler Faucet

- Hot Water Supply Only
- Requires **-M** Manifold Drain Assembly
- Faucet Location To Be Specified When Ordering

**K-49 \$371**



#### 3-Phase Upgrade

Upgrade 240 volt units to 3 Phase Wiring.

**SU-72 \$470** Per Unit



#### Thermostatic Controls

Add The Suffix **-T** To The Model Number And Add Additional Pricing Below.

**\$213** Per Well